

Product information

megol Motorenoel UHPD Truck SAE 5W-30



Description

Low viscosity engine oil of the latest generation. Due to its outstanding attributes it is for use in all commercial vehicle diesel engines, under all operating conditions and all environmental stresses (all-year oil). Advanced additive technology, in association with Hydrocrack base oils, guarantee outstanding wear protection properties and enable maximum oil change intervals. Can be mixed with all commercially available engine oils. Recommended for use with diesel engines only.

In the case of longer oil-change intervals, comply with the rules of the vehicle manufacturers!

Approvals

ACEA E4 • ACEA E7 • Mack EO-N • MAN M 3277 • MB-Approval 228.5 • Renault Trucks RLD-2 • Scania LDF-3 • Volvo VDS-3

Meguin also recommends this product for vehicles that are subject to the following specifications

API CF • DAF • IVECO 18-1804 • MTU Typ 3 • Renault Trucks RD-2 • Renault Trucks RLD • Renault Trucks RXD

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	70 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	169 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	224 °C DIN ISO 2592
Total base number	15,4 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	<= 2,0 g/100g DIN 51575
Color number (ASTM)	L4,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	9492 D-GB
200 l Drum sheet metal	9490 D-GB
1 l Bulk goods	9270 D-GB