

Top Tec MTF 5200 75W-80

Description

Low-viscosity high-performance transmission fluid with excellent high pressure and wear protection properties. Multi-purpose. Reduces friction, lowers fuel consumption and emissions and ensures smooth shifting operations. The outstanding thermal and oxidative stability guarantees a clean transmission and a long oil service life.



Properties

- excellent high-pressure and wear protection properties
- saves fuel and reduces pollutant emissions
- reduces gearshift resistance
- excellent synchronous behavior
- optimum stability to aging
- outstanding resistance to oxidation

Approvals

API GL4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW 83 22 0 309 031 • BMW 83 22 0 403 247 • BMW MTF LT-2 • BMW MTF LT-4 • Ford WSD-M2C 200-C • GM 1940764 • GM 1940768 • Nissan MT-XZ • Nissan MT-XZ TL (JR Type) • Peugeot Citroen (PSA) B71 2330 • Special Honda MTF-II • Toyota • Volvo 97308

Technical data

| | |
|----------------------------------|--|
| SAE class (gear oils) | 75W-80 SAE J 306 |
| Density at 15 °C | 0,855 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 53 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 9,2 mm ² /s ASTM D 7042-04 |
| Viscosity at -40 °C (Brookfield) | < 150000 mPas ASTM D 2983-09 |
| Viscosity index | 156 DIN ISO 2909 |
| Pour point | -42 °C DIN ISO 3016 |
| Flash point | 216 °C DIN ISO 2592 |
| Color number (ASTM) | L 2,0 DIN ISO 2049 |

Areas of application

Developed for use in transaxles, manual transmissions and transfer cases. Recommended particularly for BMW, Ford, GM/Opel, Honda, Nissan, Toyota/Peugeot/Citroën (PSA), Volvo and vehicles from other manufacturers.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

| | |
|-------------------------|---------------------|
| 1 l Can plastic | 20845 D-GB-I-E-P |
| 1 l Can plastic | 21688 PL-H-RO-TR |
| 20 l Canister plastic | 20846 D-GB-I-E-P |
| 60 l Black plate barrel | 20847 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.