

# Product information

## 2T Motoroil Race Tec

PI 18/12/02/2022



### Description

High-performance 2-stroke motor oil on an ester basis. Specially adapted to the extreme demands of sports and racing. Approved by the FIA for karting. Can be used for fuels of any kind, except methanol, etc.

### Properties

- excellent, almost residue-free combustion
- keeps piston rings and exhaust ports free of deposits
- the good cleaning properties keep the piston crown and cylinder head in particular clean
- ensures a clean wash pattern
- very high oil film stability and adhesion properties
- high temperature resistance for extreme loads
- blue coloring for easy recognition of the mixture

### Available pack sizes

1 l Canister plastic 21633  
D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Specifications / Approvals

API TC • ISO L-EGD • JASO FD

### Technical data

Density at 15 °C	0,925 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	107 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	14,2 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	135 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Total base number	2 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	blau

### Areas of application

For self-mixing (mixed lubrication) in air and water-cooled 2-stroke engines on motocross and street bikes, karts, scooters, etc.

### Application

Add contents of the can to fuel according to desired mixture ratio.

### Available pack sizes