

LM 50 Litho HT

Description

LM 50 Litho HT is a work stable, water-resistant, oxidation and corrosion resistant, high-performance lithium-complex soap grease. It ensures a very high standard of wear protection and a high load-carrying capacity.

Properties

- high capacity
- wide operating temperature range
- highest load-carrying capacity
- optimum stability to aging
- friction and wear reducing
- good corrosion protection
- universal application

Technical data

Saponification type	Lithium complex soap
Brief description	KP2N-30 DIN 51502
NLGI number	2 DIN 51818
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	>260 °C DIN ISO 2176
Oil separation after 7 days at 40 °C	2,7 % DIN 51817
Oil separation after 18 hours at 40 °C	0,8 % DIN 51817
Flow pressure at -30 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1
Four-ball tester material load/weld force	2800/3000 N DIN 51350 Teil 4
Four-ball tester wear/indentation diameter	0,6 mm DIN 51350 Teil 5
Base oil	
Viscosity at 40 °C	210 mm ² /s ASTM D 7042-04
Flash point	246 °C DIN ISO 2592
Pour point	-24 °C DIN ISO 3016



Areas of application

For lubrication of high-load bearing plain and roller bearings such as wheel bearings or greased industrial transmissions.

Application

Before treating with LM 50 Litho HT, the components must be clean and free from residues such as lubricants, dirt and moisture. Full performance is only realised when used alone.

Available pack sizes

1 kg Can sheet metal	3407 D-GB-F-E-NL
5 kg Bucket plastic	3400 D-GB
25 kg Bucket plastic	3405 D-GB
400 g Cartridge plastic	3406 D-GB-F-E-NL
400 g Cartridge plastic	7569 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.