

Maintenance Spray, white

Description

Maintenance Spray White is an adherent, waterproof, white, high-performance lubricant. After the solvent has evaporated, the product leaves a soft film of grease.

Properties

- outstanding lubricating action
- good water resistance
- lasting corrosion protection
- excellent high and low temperature behavior
- reduces fretting corrosion
- high bond strength
- clean application
- prevents friction corrosion
- silicone-free

Technical data

Color / appearance	white
Base	Mineralöl, Festschmierstoffe
Thickener	Bentonit
Density	ca. 1,0 g/cm ³
ISO 2176	NLGI 2
Consistency modifiers	without
Operating temperature range	-30 to +250 °C
Propellant	propane, butane
Odor	characteristic
Form	liquid, aerosol
Flash point	-97 °C
Density at 20 °C	0,64 g/ml

Areas of application

For lubricating moving parts such as shafts, hinges, joints, bolts, Bowden cables, slide rails, chains, springs, lock strikers, etc.

Application

Shake can before use. Spray large areas without the capillary tube from a distance of about 20-25 cm. The capillary tube eases use in places which are not very accessible. **Note: After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.**

Available pack sizes

50 ml Can aerosol	7556 D-RUS-UA
250 ml Can aerosol	1839 D-NL-F-GR-ARAB



Available pack sizes

250 ml Can aerosol	2872 GB-DK-FIN-N-S
250 ml Can aerosol	3075 D-GB-E-P
250 ml Can aerosol	3953 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.