

Product information

Meguin Gleitoel CGLP 150



Description

Lubricant with outstanding lubrication properties. Selected base oils combined with up-to-date additive technology guarantee the optimum anti-wear properties, prevent stick-slip and provide the highest level of adherence even under mixed friction conditions. Predominantly used as a machine tool oil, slideway oil and for lubricating heavy-duty reciprocating frame saws. It stands out in particular for its good demulsification capacity in relation to cooling lubricants.

Approvals

Schmieröl DIN 51502 CGLP 150

Characteristic data

ISO viscosity class	VG 150 DIN 51519
Density at 15 °C	0,895 g/cm ³ DIN 51757
Viscosity at 40 °C	150 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,7 mm ² /s ASTM D 7042-04
Viscosity index	97 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	256 °C DIN ISO 2592
Foaming behavior at 24 °C	0/0 ml ISO 6247
Foaming behavior at 93.5 °C	0/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	0/0 ml ISO 6247
Corrosion effect on steel	0-A DIN ISO 7120
Corrosion effect on copper	1-100 A3 DIN EN ISO 2160
Sulfate ash	0,3 g/100g DIN 51575
FZG gear rig test, standard test A/8, 3/90	Schadenskraftstufe >12, Spez.Gew.Änderung <0,3 mg/KWh DIN 51354 Teil 2
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

200 l Drum sheet metal 8656
D-GB

Available pack sizes

20 l Canister plastic 8655
D-GB