Product information
Top Tec 4410 5W-30

PI 19/09/14/2026

Description
Especially suited for Renault.
High-tech low-friction motor oil based on synthetic technology. Prevents undesirable deposits, ensures reliable lubrication, maximum protection and the best performance. Enables fast penetration of the oil to the engine and turbocharger.



Properties
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- outstanding lubrication reliability
- optimum stability to aging
- rapid oil penetration
- prevents the build-up of deposits
- excellent high-pressure and wear protection properties

Specifications / Approvals
ACEA C3 • MB-Approval 226.52 • Renault RN 17

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
Renault RN 0700* • Renault RN 0710* • *except Renault Sport/Alpine

Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,855 g/cm³ DIN 51757
Viscosity at 40 °C	73,0 mm²/s ASTM D7042
Viscosity at 100 °C	12,4 mm²/s ASTM D7042
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity index	165 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Evaporation loss (Noack)	9,7 % CEC-L-40-A-93
Total base number	8,5 mg KOH/g DIN ISO 3771

Technical data

Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application
For all gasoline engines (except RS and Alpine), all diesel engines without DPF and diesel engines with DPF as of model year 2018. Suitable for turbochargers and catalytic converters.

Application
The specifications and instructions from the unit or vehicle manufacturer must be followed. Full effectiveness only achieved when the product is not mixed.

Available pack sizes

1 l Canister plastic	21402 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21403 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21404 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21399 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Bag-in-Box	21961 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21400 DE-EN-ES-FR-IT-PT

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Top Tec 4410 5W-30

PI 19/09/14/2026

Available pack sizes

205 l Black plate barrel	21401 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com