

## Top Tec 6610 0W-20

### Description

Premium low-friction motor oil based on synthetic technology. Ensures optimum lubrication and outstanding lubricating film stability as well as minimum wear and the smallest deposits even under extreme loads. Ideally suited for engines with start/stop system. Guarantees maximum performance with low fuel consumption.

### Properties

- outstanding engine cleanliness
- optimum stability to aging
- tested for turbochargers and catalytic converters
- high lubrication reliability
- high shear stability
- excellent wear protection
- excellent high and low temperature behavior
- saves fuel and reduces pollutant emissions
- smooth engine running
- optimum oil pressure under all operating conditions
- long engine service life

### Specifications / Approvals

ACEA C5 • API SP • Ford WSS-M2C 952-A1 • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • Opel OV 040 1547 - A20

**LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:**

GM dexos D

### Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	39 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-42 °C DIN ISO 3016



### Technical data

Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

### Areas of application

For gasoline and diesel vehicles. Specially developed for the requirements of Ford, Jaguar/Land Rover, Mercedes-Benz, Opel, GM and other manufacturers.

### Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

### Available pack sizes

1 l Canister plastic	21660 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21661 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21662 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21663 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21664 DE-EN
205 l Black plate barrel	21666 DE-EN

## Product information

PI 20/09/29/2025



Top Tec 6610 0W-20

**Our information is based on thorough research and may be considered reliable, although not legally binding.**