

## Motorbike Fork Oil 7,5W medium/light

### Description

Full synthetic fork oil and shock-absorber oil. Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum drivability and damping. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.



### Properties

- good corrosion protection
- prevents seals from swelling
- prevents foam formation
- high wear resistance
- increases driving safety

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Technical data

Density at 15 °C	0,825 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	22,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	4,75 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	139 DIN ISO 2909
Pour point	-54 °C DIN ISO 3016
Flash point	234 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

### Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheeled vehicles.

### Application

Follow the instructions of the telescopic fork, shock absorber and two-wheeled vehicle manufacturers.

### Available pack sizes

500 ml Can plastic	3099 D-GB-I-E-P
500 ml Can plastic	5940 D-F-I-GR
1 l Can plastic	2719 D-GB-I-E-P
20 l Canister plastic	3017 D-GB