Product information

PI 21/08/17/2026

Care and Lubricating Spray



Description

Silicone-free care and lubricating spray for the lubrication, assembly and maintenance of plastic and rubber parts. Ideally suited for paint-sensitive areas. The high UV protection prevents premature aging and embrittlement of the components. Eliminates and prevents rattling and squeaking noises, particularly between plastic parts. Expels water and moisture, does not resinify or become sticky. Transparent and for universal use.

Properties

- universal application
- silicone-free
- outstanding thermal stability
- care and protection
- does not resinify or become sticky
- extremely high UV resistance

Technical data

Base	mineral oil
Propellant	propane, butane
Odor	characteristic
Color / appearance	colourless
Form	aerosol
Operating temperature range	-10 to +120 °C

Areas of application

Automotive area: For all assembly work on plastic or rubber parts. For the care and maintenance of plastic surfaces as well as the lubrication of slip rails, window guides, rollers of seat belts and as a care agent for door seals. Facilitates the assembly of plastic parts together.

Industrial area: Thanks to the formulation without silicone, no problems occur with subsequent painting. Ideal for the assembly and maintenance of plastic parts if a silicone film is not wanted. Ideal for slip rails, millers and saw blades. Expels water and moisture. Eliminates rattling and squeaking noises in all polymer alloys.

⚠ 0

Application

Spray evenly but sparingly onto the surfaces to be treated from a distance of approx. 20-30 cm. Wipe off with a dry cloth if necessary and allow to dry. Do not spray onto pedals or the steering wheel.

Available pack sizes

400 ml Can aerosol	20665 DE-EN-ES
400 ml Can aerosol	21475 DA-EN-FI-NO-SV

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com