Product information
Screw Grip

PI 22/09/22/2026



Description

Paste-like fluid which significantly boosts the static friction between the tool and the screw or nut being turned. Screwed connections which are hard to reach can therefore be protected from damage and screws which have already been damaged can be unscrewed easily.

The treated product contains biocides as protective agents.

Properties

- simple to use
- also suitable for overhead work
- no materials on the tool wallet
- clean application
- increases the friction

Technical data

Base	hard crystals of various different grain sizes
Color / appearance	grey
Form	grained
Odor	characteristic
Shelf life in original sealed container	60 months

Areas of application

Suitable for unscrewing all screws including slot, cross-head, Torx, hexagon socket and hexagon head screws.

Application

Shake well before use. Place a single drop in or around the damaged screw head. Repeatedly accurately position and move tool so that the crystals anchor into each other. The tool will soon find its grip and the screw can be loosened without any difficulty.

Available pack sizes

20 g Blister	3811 DE

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com