Product information
Rapid Cleaner Pro

PI 22/11/10/2026



Description
A combination of selected acetone-free solvents for the rapid, efficient cleaning and degreasing of components in motor vehicles and industrial applications. The low surface tension of this product gives it excellent penetration properties, enabling it to dissolve oil, grease, resin and tar residues and contaminants easily, even in hidden areas. After the solvent has evaporated, the surface is left free of grease and residues.

Properties
- universal application
- dissolves resin and tar-type residues
- low surface tension
- high proportion of active components
- optimum penetration capacity
- for cleaning heavily contaminated parts
- fast evaporation free of residues

Technical data

Color / appearance	colourless
Base	solvent-mixture, acetone-free
Form	liquid, aerosol
Propellant	CO2
Shelf life in original sealed container	60 months

Areas of application
Range of automotive applications: Rapid Cleaner offers a wide range of possible applications thanks to its universal applicability.
Brakes: Drum and disk brakes, linings, shoes, cylinders, springs and pads.
Clutch: Clutch linings, pressure plate and clutch components in general.
Transmission: Automatic gear change, planet carriers, oil pump, brake bands, clutches and gearwheels.
Assembly and repair: Carburetor, gasoline pump, engine components, electrical systems such as controllers, generator/alternator, starter; removes oil and grease spots from floor coverings, materials and linings.

Application
Spray contaminated components and allow to drain. After the solvent has evaporated, the components will be clean and free of grease.
Note: Product may attack paints and plastic components. Check for compatibility before using.

Available pack sizes

Available pack sizes

500 ml Can aerosol	3368 EN-PL-RU-TR-UK
500 ml Can aerosol	20849 CS-HR-SK-SL-SR
500 ml Can aerosol	21269 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com