

Motorbike Shock Absorber Oil

Description

Mineral shock absorber oil. Prevents the build-up of deposits and reduces friction and wear. Suppresses foaming even under the toughest operating conditions. Absolutely compatible with gaskets. The unique formulation ensures a better feeling of contact between the tires and the road, enhancing both safety and the pleasure of riding.

Properties

- increases driving safety
- high wear resistance
- prevents the build-up of deposits
- outstanding viscosity stability
- very compatible with seals
- outstanding corrosion protection
- prevents foam formation

Technical data

ISO viscosity class	VG 15 DIN 51519
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	15,3 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	3,5 mm ² /s ASTM D 7042-04
Viscosity index	106 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	194 °C DIN ISO 2592
Demulgation characteristics at 54 °C	< 20 min DIN ISO 6614
Foaming behavior at 24 °C	30/0 ml ISO 6247
Foaming behavior at 93.5 °C	0/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	40/0 ml ISO 6247
Color / appearance	blue

Areas of application

Universal use in shock absorbers on motorbikes, mopeds, motor-assisted bicycles and other two-wheelers.

Application

Note the shock absorber and two-wheel vehicle

manufacturers' operating instructions.

Available pack sizes

1 l Can plastic	20960 D-GB-I-E-P
20 l Canister plastic	20961 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

