

Bike Tire Fix

Description

Special combination of active agents for first aid in the event of punctured tires. Repairs flat tires without the need for removal. Not suitable for use on tubes that ripped or cut at the side, or if the tire has slipped off the rim.

Properties

- subsequent tire repair possible
- rapid remedy for punctures without dismantling
- simple to use

Technical data

Base	Rubber solution
Color / appearance	whitish
Odor	characteristic
Propellant	propane, butane
Shelf life in original sealed container	24 Monate

Areas of application

For the repair of bicycle tires (with or without inner tube) from 12 – 29 inches. Can be used for all common bicycle valves (Schrader, Presta valve and Dunlop valves). Also suitable for e-bikes.

Comment

Do not forget to go to a workshop to have the tire professionally repaired.

Application

Where possible, remove any causes of the puncture first (e.g. nails, screws). Then bring the wheel with the valve into the 12 o'clock position and deflate fully. Shake the can well, screw the screw connector onto the tire valve, hold the can vertical and use the entire can. Then remove the can and wipe off excess material. Finally, adjust the tire air pressure and take off immediately so that the foam can be distributed evenly. Depending on the size of the puncture, it may be necessary to pump more air after a few minutes. In most cases, a solid plug sealing the hole will have formed after 10 minutes.

Available pack sizes

75 ml Can aerosol 20719
GB-DK-FIN-N-S

75 ml Can aerosol 6056
D-GB-E-F-I



Our information is based on thorough research and may be considered reliable, although not legally binding.