

Product information

Cable Grease (Spray)

PI 23/12/01/2021



Description

High-quality lubricant for the preservation of wire cables. Thanks to its excellent corrosion protection, it is also suitable for cavity sealing and underfloor protection in the automotive sector.

Properties

- excellent corrosion protection
- drives out moisture
- has a lasting effect
- excellent penetration action
- highest load-carrying capacity
- optimum effectiveness when the product is used unmixed
- no aromatic hydrocarbons
- high bond strength

Technical data

Color / appearance	brown
Flash point	-60 °C
Dropping point	> 85 °C
Base	additives, polymers
Viscosity at 40 °C	22 mm ² /s
Form	aerosol, liquid
Odor	characteristic
Shelf life in original sealed container	30 Monate
Recommended storage temperature	10 - 30 °C

Areas of application

For preventive preservation of wire cables. Also suitable for the cavity sealing and underfloor protection of vehicles.

Comment

Shake before using. After use, clear spray nozzle by inverting the can and spraying until only the propellant emerges.

Application

The parts to be treated must be dry and free of dirt and rust. Shake well before use. The aerosol is sprayed onto the wire cables. After use, the valve of the can should be sprayed empty upside down until only propellant gas escapes!

Use of the Cavity Seal Spray Probe (part no. 6208) is possible.

Available pack sizes



Available pack sizes

500 ml Can aerosol 6135
D-GB-I-E

Our information is based on thorough research and may be considered reliable, although not legally binding.