

Diesel Smoke Stop Concentrate

Description

Highly effective additive for diesel fuels. Minimizes soot emissions from diesel engines by accelerated soot combustion, thus reducing unpleasant odors and impairment of visibility. Maintains engine performance and reduces the frequency of repairs.

Properties

- no smell
- protects the environment
- improves the turbidity value
- keeps injection nozzles clean
- reduces soot emissions
- assures a clear view and safety
- does not contain heavy metals
- high engine cleanliness
- good corrosion protection
- self mixing
- prevents seizing and the injector needles from gumming up

Technical data

Shelf life in original sealed container	36 months
Mineral oil content	94,98 %
Color / appearance	black
Odor	characteristic
Density at 20 °C	0,8025 g/cm ³
Flash point	>63 °C

Areas of application

For all passenger vehicle and truck diesel engines as well as agricultural, forestry and stationary diesel engines. Only suitable for engines without DPF.

Application

250 ml sufficient for 200 l of diesel fuel. Add the contents of the can directly before refueling.

Available pack sizes

250 ml Can sheet metal	2521
	D-E-P
250 ml Can sheet metal	7179
	GB-GR-I
205 l Black plate barrel	2519
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

