Product information
Weld Protection Spray

PI 24/10/01/2026



Description
Prevents adhesion of welding beads on the workpiece and the torch without impairing the weld. Increases the service life of the welding nozzles and the inner components of the torch. Silicone-free.

Properties
- increases service life
- silicone-free
- prevents adhesion of welding beads on the workpiece and the torch
- suitable for steel, aluminum and stainless steel

Technical data

Color / appearance	white
Form	liquid, aerosol
Propellant	propane, butane
Base	talc
Solubility in water	insoluble
Odor	characteristic

Areas of application
For all welding work on steel, aluminum and stainless steel.

Comment
Shake can regularly during extensive use. After use, clear spray nozzle (hold can with spray head upside down) by spraying until only pure propellant emerges.

Application
Briefly shake aerosol can. Switch off the welding equipment and spray a thin coat on cold workpieces and torches.
Note: Do not spray onto workpieces or parts of the torch while still hot or glowing. Allow an airing time of at least 5 minutes.

Available pack sizes

500 ml Can aerosol	4086 DE-EN-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com