

Product information

megol Motorenöl SHPD SAE 15W-40 TBN20



Description

Modern engine oil for commercial engines, under all operating conditions and all environmental stresses (all-year oil). It fulfils the highest demands that modern diesel engines currently place on engine oils. Advanced additive technology guarantees outstanding low-viscosity and wear protection properties and enables maximum oil change intervals.

Specifications / Approvals

ACEA A3/B4, E7 • API CH-4 • API SL

Available pack sizes

200 l Black plate barrel 33080
D-GB

Meguin also recommends this product for vehicles that are subject to the following specifications

MB 228.3 • Volvo VDS-2 • MAN M 3271-1 • Cummins CES 20076 • Cummins CES 20077 • Mack EO-M Plus • Renault Trucks RD-2 • MTU Typ 2

Characteristic data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,88 g/cm ³ DIN 51757
Viscosity at 40 °C	102 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	139 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10,5 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	20 mg KOH/g DIN ISO 3771
Sulfate ash	2,7 g/100g DIN 51575
Color number (ASTM)	L5,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic 8416
D-GB