

Chain lubrication oil for forklift trucks

Description

High-quality, thermostable, adherent and synthetic lubricant compound. With selected white solid lubricants that provide additional lubrication properties and show where the product has been applied. Suitable for all types of chains. Reduces chain elongation thanks to high pressure absorption capacity.



Properties

- excellent adhesion
- excellent creep properties
- outstanding corrosion protection
- optimum effectiveness when the product is used unmixed
- especially cold, hot and splash-water resistant
- high pressure-absorption capability
- reduces chain elongation
- reduces friction and prevents stick slip

and may be considered reliable, although not legally binding.

Technical data

Color / appearance	colourless, clear
Base	oil with adhesion improver
Operating temperature range	-30 to +180, short periods up to 200 °C
Water resistance at 90 °C	0 DIN 51 807
Form	aerosol, liquid
Odor	characteristic
Shelf life in original sealed container	60 months

Areas of application

For initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Ideal for high-load chains thanks to extremely good adherence.

Application

Carefully clean chains with solvent. Then spray with chain lubrication oil. The lubricant attains its final consistency and adherence once the solvent has evaporated.

Available pack sizes

400 ml Can aerosol 20946
DE-EN-ES-IT-PT

Our information is based on thorough research