Product information
Brake Anti-Squeal Spray

PI 24/02/11/2026



Description

Specially developed lubricating and separating spray made from synthetic and ceramic agents. Eliminates squealing noises that occur between brake pistons or contact surfaces and the brake lining.

Properties

- good corrosion protection
- eliminates squeaks
- outstandingly adherent
- easy to use
- extremely low friction
- outstanding thermal stability
- resistant to road salt and splash water
- ideally suited as a separating paste

Technical data

Form	areosol, liquid
Base	synthetic and ceramic materials
Color / appearance	light blue
Maximum tear strength	-40 bis +200 kurzfristig bis +250 °C
Risk of frost damage	-40 bis +1200 °C
Odor	characteristic

Areas of application

For fitting, repair and maintenance work on brake systems. Used for basic lubrication and as a preventive measure against brake squeals. Highly suitable as a universal spray for numerous applications apart from brake systems.

Comment

Do not under any circumstances allow the spray to get onto the friction surface of the brake lining or the brake disk.

Application

With floating brake calipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Also clean off coarse contaminants on used brake linings, pins and cross springs. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After the solvent has evaporated, spray the cleaned parts with the spray on all sliding surfaces, channels and contact surfaces. After the propellant has evaporated, repeat the process if necessary.

Available pack sizes

400 ml Can aerosol	3079
	DE-EN-ES-IT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com