

### Description

Speed Petrol Additive consists of a combination of ash-free, self-lubricating active agents which have been formulated according to the latest fuel and additive technology. This product is characterised by its outstanding cleaning and material protection properties.

### Properties

- for carburetor and fuel-injection engines
- reduces residue
- normalizes gasoline consumption and exhaust emissions
- highly economical
- reduces the risk of knocking combustion
- prevents the build-up of deposits
- keeps the fuel system clean
- tested for turbochargers and catalytic converters
- increases operational reliability
- good corrosion protection

### Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm <sup>2</sup> /s
Density at 15 °C	0,765 g/cm <sup>3</sup>

### Areas of application

Speed Petrol Additive is added to the fuel of all 2-stroke and 4-stroke gasoline engines for successful results. This applies to engines in motor vehicles and ships and industrial applications. As well as being used while the engine is running, Speed Petrol Additive can be used for preserving engines when laid up for long periods.

### Application

1 litre is sufficient for 400 litres of gasoline. 1 measuring cup (integrated in the screw cap) is sufficient for 10 litres of gasoline. The product mixes with the gasoline automatically.

### Available pack sizes

1 l Can sheet metal	5105
	D

### Available pack sizes

195 l Drum sheet metal	4054
	GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

