Product information

PI 25/09/22/2026

Maintenance Spray, white

Description

Maintenance Spray White is an adherent, waterproof, white high-performance lubricant. After the solvent has evaporated, the product leaves a soft film of grease.

Properties

- excellent high and low temperature behavior
- good water resistance
- outstanding lubricating action
- silicone-free
- clean application
- high bond strength
- lasting corrosion protection
- reduces fretting corrosion
- prevents friction corrosion

Technical data

Color / appearance	white
Base	Mineralöl, Festschmierstoffe
Thickener	Bentonit
Density	ca. 1,0 g/cm³
ISO 2176	NLGI 2
Consistency modifiers	without
Operating temperature range	-30 to +250 °C
Propellant	propane, butane
Odor	characteristic
Form	liquid, aerosol
Density at 20 °C	0,64 g/ml

Areas of application

For lubricating moving parts such as shafts, hinges, joints, bolts, Bowden cables, slide rails, chains, springs, lock strikers, etc.

Application

Shake can before use. Spray large areas without the capillary tube from a distance of about 20-25 cm. The capillary tube eases use in places which are not very accessible. **Note: After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.**

Available pack sizes

250 ml Can aerosol	1839 AR-DE-EL-FR-NL
250 ml Can aerosol	2872 DA-FI-NO-SV

Available pack sizes

250 ml Can aerosol	3075 DE-EN-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com