

# Product information

## Meguin Getriebeoel CLP 68



### Description

EP lubricant with outstanding lubrication and wear protection properties. Manufactured from high-quality base oils and the latest sulfur-phosphorus additives. Suitable for use in industrial transmissions and roller and plain bearings subjected to high pressures and, in particular, large-scale plants with circulation lubrication systems.

### Approvals

Schmieröl SEB 181 226 CLP 68 • Schmieröl DIN 51517 CLP 68

### Characteristic data

ISO viscosity class	VG 68 DIN 51519
Density at 15 °C	0,865 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	68 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	102 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	226 °C DIN ISO 2592
Neutralization number	0,5 mg KOH/g DIN 51558 T1
Demulgation characteristics at 54 °C	15 min DIN ISO 6614
Foaming behavior at 24 °C	0/0 ml ISO 6247
Foaming behavior at 93.5 °C	0/0 ml ISO 6247
Foaming behavior at 24 °C after 93.5 °C	0/0 ml ISO 6247
Air separation capacity	10 min DIN ISO 9120
Corrosion effect on steel	0-B DIN ISO 7120
Corrosion effect on copper	1-125 A3 DIN EN ISO 2160
FZG gear rig test, standard test A/16, 6/90	Schadenskraftstufe >12, Spez.Gew.Änderung <0,27 mg/KWh DIN 51354 Teil 2
Color number (ASTM)	L1,0 DIN ISO 2049

### Available pack sizes

20 l Canister plastic	4387 D-GB
200 l Drum sheet metal	6372 D-GB
1.000 l Deposit container	9544 D-GB