

Product information

megol Motorenoel Universal SAE 20W-50



Description

Multigrade motor oil that is suitable for use in both passenger car and commercial vehicle fleets as a universal oil. Ideal lubricant for gasoline engines with and without catalytic converter and for diesel engines, including those with a turbocharger.

Note the manufacturer's instructions!

Approvals

ACEA A3 • ACEA B4 • ACEA E2 • API SL • API CG-4 • Allison C4 • Caterpillar TO-2 • MIL-L 2104 E

Meguin also recommends this product for vehicles that are subject to the following specifications

MAN 271 • MB 228.3

Characteristic data

SAE class (engine oils)	20W-50 SAE J300
Density at 15 °C	0,880 g/cm ³ DIN 51757
Viscosity at 40 °C	165,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	18,5 mm ² /s ASTM D 7042-04
Viscosity at -20 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -15 °C (CCS)	≤ 9500 mPas ASTM D5293
Viscosity index	125 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	7,2 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L5,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	9628 GB-F-E-P-NL-ARAB
4 l Canister plastic	9148 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	4381 D-GB-F-HR-RUS-GR
20 l Canister plastic	6484 D-GB
60 l Drum sheet metal	6863 D-GB
200 l Drum sheet metal	6485 D-GB
1 l Bulk goods	6864 D-GB

Available pack sizes

1 l Canister plastic	4384 D-GB-F-HR-RUS-GR
----------------------	--------------------------