

Product information

Cable Grease (Spray)

PI 27/04/09/2026



Description

High-quality, universal, solvent-based corrosion protection wax in the automotive sector. Especially suitable for use as cavity and underbody protection. Forms a matt, closed, and sticky coating. Attention: Not suitable for handling wire cables. Product should always be stored and transported free of frost.



Properties

- outstanding corrosion protection
- high bond strength
- drives out moisture
- excellent creep properties
- has a lasting effect
- optimum effectiveness when the product is used unmixed
- silicone-free
- no aromatic hydrocarbons

6208) is possible.

Available pack sizes

500 ml Can aerosol 6135
DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Color / appearance	brown
Dropping point	> 85 °C
Base	additives, polymers
Viscosity at 40 °C	22 mm ² /s
Form	aerosol, liquid
Odor	characteristic
Shelf life in original sealed container	30 months
Recommended storage temperature	10 - 30 °C

Areas of application

For the preventative preservation of vehicles, machines, and add-on parts made of iron and steel alloys as well as light and non-ferrous metals. Thanks to its excellent corrosion protection, it is suitable for cavity sealing and underfloor protection in the automotive sector

Comment

Not suitable for handling wire cables. Attention: Product should always be stored and transported free of frost.

Application

The parts to be treated must be dry and free of dirt and rust. Shake well before use. Optimum creep effect at an application temperature of +25 °C. An adherent film is formed after the solvent evaporates. The relevant manufacturer's instructions must be observed. After use, the valve of the can should be sprayed empty upside down until only propellant gas escapes. Use of the Cavity Seal Spray Probe (part no.