

ATF Additive

Description

The additives contained provide optimal care of rubber and plastic seals in the steering gear and automatic transmission. Leaks on transmissions caused by hardened or brittle seals are prevented or remedied. Holes and ducts in the gears are also cleaned, and the performance of the oil is revitalized. The noise generation of power steering systems is reduced and the shifting operations of automatic transmissions are improved. Can extend the service life of steering gears and automatic transmissions and lower the repair costs.



Available pack sizes

250 ml Tube plastic 8336
AR-EN-FR

Properties

- high wear resistance
- prevents oil loss
- minimizes unwanted noise
- cleans and maintains
- regenerates seals
- prevents rapid aging of oil
- increases service life
- stable to oxidation
- care and protection
- prevents expensive repairs
- damps shifting operations

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Color / appearance	brown
Viscosity at 40 °C	~ 166 mm ² /s DIN 51562
Viscosity at 100 °C	~ 26 mm ² /s DIN 51562
Density	0,888 g/ml
Refractive index at 20 °C	~ 1,478
Form	liquid
Odor	characteristic

Areas of application

Suitable for all steering gears and automatic transmissions that are filled with ATF II and ATF III oils.

Application

Mix additive into the gear oil using the dipstick. Contents (250 ml) sufficient to treat up to 8 liters of oil.

Available pack sizes

250 ml Tube plastic	2702 AUEN-EN
250 ml Tube plastic	5135 DE-EN-ES-IT-PT