

Pro-Line Oil Leak Stop

Description

Rejuvenates rubber and plastic seals in the engine and reduces oil consumption via piston rings and valve guides. The additive counteracts the loss in viscosity in motor oils. Puts an end to environmentally pollutant oil patches on the road and in the garage. Compatible with all commercially available motor oils.

Properties

- prevents blue, smoky exhaust fumes
- suitable for gasoline and diesel engines
- maintains and regenerates rubber and plastic seals
- outstanding elastomer compatibility
- guarantees low oil consumption
- prevents oil leaks and pollution of the environment
- reduces engine noise
- remedies leaks at shrunken or porous seals

Technical data

Color / appearance	orange, clear
Appearance / properties	viscous liquid
Viscosity at 40 °C	133,81 mm ² /s
Flash point	112 °C DIN ISO 2592
Pour point	-5 °C DIN ISO 3016
Form	pastelike, liquid
Odor	characteristic

Areas of application

Suitable for all gasoline and diesel engines.

Application

Contents of the can (1 liter) are sufficient for up to 15 liters of motor oil. The product can be added at any time. After adding, run the engine until warm or drive the vehicle. Sealing first takes place after about 600 to 800 km of driving. To guarantee a lasting effect, we recommend using the additive again after each oil change.

Note: Not suitable for use in motorcycles with wet clutches!

Available pack sizes

1 l Can sheet metal 5182
D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

