

Tractor Oil STOU 10W-40

Description

Tractor Oil STOU (Super Tractor Oil Universal) is a universal oil which has been specially developed for agricultural machines. This product is designed to match the features and meet the requirements of different tractor specifications for engine, manual and axle transmissions, hydraulic systems, fluid flywheels and wet brakes.



Properties

- high wear resistance
- high pressure-absorption capability
- outstanding oil film strength
- good cold-start behavior
- guarantees smooth gearshifting
- universal application
- rationalizes storage
- no risk of confusion due to similarity in products
- miscible with other universal tractor oils

Specifications / Approvals

ACEA E2 • ACEA E3 • API CF-4 • API CG-4 • API SF • API GL4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Allison C4 • Case (IHC) B6 • Caterpillar TO-2 • David Brown • Fendt • Ford New Holland M2C 84-A • Ford New Holland M2C 159-B • Ford New Holland M2C 159-C • John Deere J27 • KHD • Mack EO-K • Mack EO-K2 • Massey-Ferguson M1139 • Massey-Ferguson M1144 • Massey-Ferguson M1145 • MB 227.1 • MB 228.1 • MIL-L 2104 D • MIL-L 2105 • MIL-L 46152 B • Steyr • ZF TE-ML 06B • ZF TE-ML 07B

Technical data

Viscosity SAE class	10W-40 SAE J300
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	92 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D 5293
Viscosity index	156 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93

Technical data

Flash point	230 °C DIN ISO 2592
Total base number	11,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,6 g/100g DIN 51575
Color number (ASTM)	3 DIN ISO 2049

Areas of application

Universal oil for transmission, engine, hydraulic and immersion brakes. Suitable for high-load tractor units.

Application

The operating instructions of the tractor manufacturer must be followed. Can be mixed with all commercially available motor oils. Full effectiveness only when used unmixed.

Available pack sizes

20 l Canister plastic	4722 D-GB
60 l Black plate barrel	4703 D-GB
205 l Black plate barrel	4704 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.