

Leak Finder Spray

Description

PFAS-free leak test fluid for detecting spots where gas and compressed air may escape. Locates leaks on tanks, pipes, hoses, screw joints, welding seams, flange connections and fittings. Water-soluble and biodegradable test fluid filled with environmentally friendly propellant. Guarantees economical, reliable use thanks to the high bubble formation.



Properties

- biologically degradable
- environmentally friendly
- miscible with water
- high capacity
- forms air bubbles

and may be considered reliable, although not legally binding.

Technical data

Base	special aqueous active ingredient solution
Color / appearance	aqueous, low-viscosity liquid
Form	aerosol
Mineral oil content	0 %
Shelf life in original sealed container	24 months

Areas of application

For detection of leakage of flammable gases from family 1 (town gas), family 2 (natural gas) and family 3 (liquefied petroleum gas), for explanations see EN 437, withing a temperature range of 0 °C to 50 °C. Can also be used for other gases. Carry out preliminary tests in case of doubts.

Application

Put depressurized systems under pressure with a gas in advance. Shake can well. Then apply on the location to be checked from a distance of 30 – 50 cm (check all connection points, if possible). Observe for some time. If bubbles form, there is a leak. The smaller the bubbles, the smaller the leak. Attention: After use on copper and PVC, make sure to rinse with water!

Available pack sizes

400 ml Can aerosol	1809
	D-NL-F-GR-ARAB
400 ml Can aerosol	2836
	GB-DK-FIN-N-S
400 ml Can aerosol	3350
	D-GB-I-E-P

Our information is based on thorough research