

## Scratch Stop

### Description

Scratch Stop is a grinding paste that does not contain silicone oil and is suitable for universal use. The product can be used to remove scratches, spray mist, stress marks and uneven finishes on colour or metallic paintwork. It is also suitable for matt and blank plastic discs or polycarbonate headlamp lenses, and can be used in both manual and automated processing.



### Properties

- prepares surfaces for painting
- easy removal of weathered paint layers
- silicone-free
- simple to use

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Technical data

Odor	characteristic
Form	pastelike, liquid
Flash point	>61 °C
Density at 20 °C	1,08 g/ml
pH value	7,8
Color / appearance	rose
Base	Abrasives, wax
Viscosity at 20 °C	20000-25000 mPas
Shelf life in original sealed container	30 Monate

### Areas of application

Specially developed product for removing scratches. Suitable for colour and metallic paintwork. Optimally suited for processing matt and blank plastic discs or polycarbonate headlamp lenses.

### Application

Wash the vehicle thoroughly before application. Shake the tube before use. Apply the product with a cloth or sponge and work it into the affected area under light pressure (polish with a foam buffing machine at 1,500 to 2,000 rpm). **Exercise caution during application on chassis joints, as the product is extremely abrasive.** Wipe off any polish residue using a clean cloth (preferably a microfibre cloth). After the procedure is completed, seal the paintwork surface using Universal Polish (part no. 1679).

### Available pack sizes

200 ml Tube plastic	20887
	JP
200 ml Tube plastic	2320
	D-GB-F-ARAB