# Product information

PI 30/11/11/2026

## Battery Clamp Grease Spray




### Description

Special grease which is compatible with plastics for the maintenance and care of vehicle electronic systems, particularly the battery terminals and electrical connectors. Ensures reliable starting and a longer battery life. Offers high corrosion protection and prevents leakage currents. Prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts.

### Properties

- good corrosion protection
- compatible with plastics
- prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts
- prevents leakage currents
- good electronic properties

### Technical data

| | |
|---|---|
| Thickener | Calciumseife |
| NLGI number | 2<br>DIN 51818 |
| Color / appearance | red |
| Form | aerosol, liquid |
| Dropping point for the solids | 100 °C<br>DIN ISO 2176 |
| Worked penetration | 265-295<br>DIN 51804 |
| Operating temperature range | -30 to +60 °C |
| Emcor corrosion class | 0/0<br>DIN 51802 |
| Odor | characteristic |

### Areas of application

Used especially for battery terminals and connections in vehicle electronic systems.

### Comment

After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

### Application

Gently shake spray can before use. Clean contaminated components and treat the surface after joining the contacts.

### Available pack sizes

| | |
|---|---|
| 300 ml Can aerosol | 3141<br>DE-EN-ES |

### Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com