

Motorbike 2T Bike-Additive

Description

Increases the performance of the engine. Removes deposits in the fuel system as well as at intake and exhaust ports and prevents new deposits from forming. Protects the entire fuel system against corrosion. Tested on engines with catalytic converters. Clean engines use less fuel and reduce the pollutant emissions.



Properties

- increases operational reliability
- tested for the use with catalytic converters
- optimizes engine performance
- environmentally friendly
- highly economical
- prevents corrosion in the fuel system
- normalizes gasoline consumption and exhaust emissions
- reduces residue
- cleans carburetors

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	> 61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,7989 g/ml

Areas of application

For all 2-stroke engines with mixture or separate lubrication.

Application

Filling the dosage chamber (25 ml) once is sufficient for 5 l of fuel or fuel mixture.

Available pack sizes

250 ml Dispensing bottle plastic	1582
	D-GB-I-E-P
250 ml Dispensing bottle plastic	20859
	JP

Our information is based on thorough research and may be considered reliable, although not legally binding.