Product information
Oil Spot Remover

PI 31/11/05/2026



Description
Special agent for fast, effective removal of stubborn, environmentally harmful oil spots on workshop and garage floors, entrances, parking spots etc.

Technical data

Base	Solvent, absorbent pigments
Color / appearance	light yellow
Odor	characteristic
Form	aerosol, liquid

Areas of application
With oil spots on absorbent and non-absorbent surfaces such as asphalt, concrete, clinker, screed and ceramic. Also ideal for analyzing oil loss at engines.

Application
Shake can vigorously before use. Then direct vertically downwards, spray onto the contaminated area from a distance of approx. 10 cm and allow to act for 20 – 30 minutes. Remove residues after the product has dried. Repeat procedure as needed. Use for oil loss analysis: Clean the engine and allow it to dry. Then spray Oil Spot Remover on the connection points of the engine and let it dry. Discoloration appears where there is leak.

Available pack sizes

400 ml Can aerosol	3315
	DE-EN-IT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com