

Product information

megol Motorenoel New Generation SAE 5W-30



Description

High-performance motor oil based on HC synthetic technology with a latest generation additive system (Low-SAPS technology). Complies with the high performance requirements of modern gasoline and diesel engines. Ensures maximum service life and function of the diesel particulate filter (DPF) as well as low wear, good engine cleanliness, long oil change intervals and low fuel consumption.

Range of applications: Passenger cars. S

APS level: Low-SAPS.

Note the manufacturer's instructions!

Approvals

ACEA C3 • API SN • BMW Longlife-04 • MB-Approval 229.51 • VW 505 00 • VW 505 01

Meguin also recommends this product for vehicles that are subject to the following specifications

Ford WSS-M2C 917-A

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	68,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≥ 6600 mPas ASTM D5293
Viscosity index	172 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	10 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,4 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575

Characteristic data

Color number (ASTM) 2,5
DIN ISO 2049

Available pack sizes

1 l Canister plastic	6512 D-GB-F-HR-RUS-GR
5 l Canister plastic	6513 D-GB-F-HR-RUS-GR
20 l Canister plastic	6696 D-GB
60 l Drum sheet metal	4609 D-GB
200 l Drum sheet metal	6697 D-GB
1.000 l Deposit container	9761 D-GB
1 l Bulk goods	6858 D-GB