

Product information

megol Motorenoel Low Emission SAE 5W-40



Description

High-performance motor oil based on HC synthetic technology with special additive system (Low-SAPS technology). Meets the high performance requirements and quality level of modern gasoline and diesel engines. In particular, it guarantees the effectiveness of the Euro 4/Euro 5 emission control systems over very long periods as well as low wear and good engine cleanliness. Particularly suitable for pump-jet engines (PD) from Volkswagen (VAG). Also for Ford Galaxy models with VAG PD engines.

Range of applications: Passenger cars.

SAPS level: Low-SAPS.

Note the manufacturer's instructions!

Approvals

ACEA C3 • API CF • API SN • Ford WSS-M2C 917-A • MB-Approval 229.31 • Porsche A40 • VW 505 00 • VW 505 01

Meguin also recommends this product for vehicles that are subject to the following specifications

BMW Longlife-04 (up to 2018) • Fiat 9.55535-S2 • GM dexos2 • Renault RN 0700 • Renault RN 0710

Characteristic data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	88 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	169 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC-L-40-A-93
Flash point	232 °C DIN ISO 2592

Characteristic data

Total base number	7,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	6573 D-GB-F-ARAB-RUS-RO-I-E-P
1 l Canister plastic	9608 GB-F-E-P-NL-ARAB
4 l Canister plastic	6675 D-GB-F-HR-RUS-GR
5 l Canister plastic	6574 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	9610 GB-F-E-P-NL-ARAB
20 l Canister plastic	6575 D-GB
60 l Drum sheet metal	6576 D-GB
200 l Drum sheet metal	6581 D-GB
1.000 l Deposit container	9746 D-GB
1 l Bulk goods	9527 D-GB