

Motorbike Foam Filter Oil (Spray)

Description

Specially developed aerosol for wetting foam and fabric air filters. Dust and dirt are reliably trapped even under extreme operating conditions and engine damage is thus avoided. Guarantees an optimal air flow and thus maximum engine output.

Properties

- waterproof
- binds dust and sand
- improves filter properties
- long engine service life
- reduces wear
- extremely adherent

Technical data

Base	polymers
Form	liquid, aerosol
Odor	characteristic
Color / appearance	blue

Areas of application

Suitable for use on all 2-stroke and 4-stroke motorcycles as well as vehicles with air or water-cooled engines using foam or fabric air filters.

Application

First free the filter of coarse contaminants by knocking them out. Clean the air filter with LIQUI MOLY Motorbike Air Filter Cleaner (part no. 1299), wait for the solvent to evaporate and coat with Motorbike Air Filter Oil (spray). Before installing the air filter, allow it to air out for 10 to 15 minutes.

When working with Motorbike Air Filter Oil (spray), make sure that the area is well ventilated!

Available pack sizes

400 ml Can aerosol	1604
	D-GB-E-P
400 ml Can aerosol	5933
	D-F-I-GR
400 ml Can aerosol	20745
	GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.

