

## Universal Oil for Garden Equipment 10W-30

### Description

Multigrade motor oil with high-quality base oils and high additive content. Ensures optimum lubrication and outstanding engine cleanliness year-round, even under the most demanding conditions. Exceeds the requirements of well-known engine manufacturers such as Briggs & Stratton, Honda, Tecumseh, etc.

### Properties

- high wear resistance
- can be used in gasoline and diesel engines with and without turbocharger
- miscible with all commercially available motor oils
- tested for the use with catalytic converters
- low evaporation loss
- very good dispersion properties
- high resistance to aging
- excellent cleaning effect
- increases the lubricating effect
- universal application

### Specifications and approvals

ACEA A3 • ACEA B3 • API CF • API SG • API SH • API SJ

### Technical data

SAE class (engine oils)	10W-30 SAE J300
Density at 15 °C	0,86 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	70 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	155 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	13 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 - 1,5 g/100g DIN 51575



### Technical data

Color number (ASTM)	L 3,0
	DIN ISO 2049

### Areas of application

For 4-stroke engines, such as lawnmowers, emergency power units, riding mowers, chippers, rotary tillers, scarifiers, string trimmers, high-pressure cleaners, snow blowers, etc.

### Application

The specifications and instructions from the assembly or equipment manufacturer must be followed.

### Available pack sizes

1 l Canister plastic	1273 D-BOOKLET
600 ml Canister plastic	7686 D

**Our information is based on thorough research and may be considered reliable, although not legally binding.**