Product information
Motorbike MoS2 Shooter

PI 33/08/18/2026



Description
Reduces friction and wear, thus reducing oil and fuel consumption. Increases the engine's running smoothness and reduces malfunctions.

Properties
- miscible with all commercially available motor oils
- reduces oil and fuel consumption
- tested for the use with catalytic converters
- smooth engine running
- increases smooth operation
- minimizes friction
- miscible with all commercially available gear oils
- prevents operational malfunctions
- reduces wear

Technical data

Base	MoS2 mineral oil
Color / appearance	black
Density at 20 °C	0,903 g/ml DIN 51757
Particle fineness of MoS2	0,3 µm
Viscosity at 40 °C	95 mm²/s
Flash point	201 °C

Areas of application

For all 2-stroke engines with separate and mixture lubrication and for all 4-stroke engines, also with wet multi-disk clutch. Also suitable for use in transmissions and final drives. Tested on engines with catalytic converters.

Application
In 4-stroke engines at every oil change; in 2-stroke engines add when filling the oil or fuel tank. Shake well before use! **Dosage:** In 4-stroke engines or in transmissions: 20 ml (1 tube) is sufficient for 1 l of motor oil. For 2-stroke engines (mixture lubrication): 10 ml per 10 l of fuel mixture or for separate lubrication 20 ml for 1 l of 2-stroke oil.

Available pack sizes

20 ml Tube plastic	3444 EN
20 ml Tube plastic	20561 ES
20 ml Tube plastic	20563 FR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com