Product information

Top Tec 4210 0W-30

PI 33/11/12/2026

Description

High-tech low friction motor oil based on fully-synthetic technology. Delivers maximum performance and optimal lubrication under all operating conditions. Reduces friction between moving engine parts and minimizes wear. The low proportion of ash-forming ingredients ensures maximum service life of the particulate filters.



Properties

- excellent high-pressure and wear protection properties
- outstanding engine cleanliness
- minimizes friction
- optimum lubrication under all operating conditions
- instant lubrication after cold start
- increases service life
- tested for particulate filters and catalytic converters
- tested for turbocharger

Specifications / Approvals

ACEA C3 • BMW Longlife-04 • BMW Longlife-19FE • MB-Approval 229.51 • MB-Approval 229.52 • Porsche C30 • VW 504 00 • VW 507 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

API SN • Iveco 18-1811 SC1 LV 21

Technical data

Viscosity SAE class	0W-30 SAE J300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	60,0 mm²/s ASTM D7042
Viscosity at 100 °C	11,9 mm²/s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	⩽ 6200 mPas ASTM D5293
HTHS at 150°C	⩾ 3,5 mPas ASTM D5481
Viscosity index	200 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592

Technical data

Evaporation loss (Noack)	10,0 % ASTM D5800 B
Total base number	8,4 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

For gasoline and diesel vehicles also particulate filter. Specially developed for vehicles of Audi, Porsche and the Volkswagen Group, which, according to the Motor Oil Strategy 2020/2021, prescribe a lubricant of this specification and viscosity in various models worldwide.

Available pack sizes

1 l Canister plastic	21604 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21605 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21606 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Bag-in-Box	21963 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21607 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	21608 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com