

Motorbike Gear Oil 10W-30

Description

High-pressure gear oil of API GL-4 performance class based on selected base oils and multifunctional additives. For universal use in a number of transmissions and final drives.

Properties

- excellent viscosity/temperature properties
- very compatible with seals
- high pressure-absorption capability
- excellent resistance to aging
- minimizes wear
- reduces running noise

Specifications / Approvals

API GL4

Technical data

SAE class (engine oils)	10W-30 SAE J 300
Density at 15 °C	0,860 g/cm ³ DIN 51757
Viscosity at 40 °C	76,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,5 mm ² /s ASTM D 7042-04
Viscosity index	145 DIN ISO 2909
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	12,9 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

For transmissions and final drives operating under normal and high load. Note the transmission manufacturer's instructions.

Application

Note the transmission manufacturer's instructions.



Mixable with all branded gear oils. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Can plastic	3087 D-GB-I-E-P
1 l Can plastic	5927 D-F-I-GR

Our information is based on thorough research and may be considered reliable, although not legally binding.