

Radiator Antifreeze KFS 12++

Description

Combination of active agents which is formulated using an ingenious selection of inhibitors based on hybrid technology. Offers outstanding protection against frost, corrosion and overheating across its entire engine service life. Amine-, borate-, nitrite- and phosphate-free radiator antifreeze based on ethylene glycol.



Properties

- outstanding corrosion protection
- contains no amines, borates, nitrites or phosphates
- protects against overheating

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Audi TL-774 G = G12++ • MAN 324 Typ Si-OAT • MB 325.5 • Seat TL-774 G = G12++ • Skoda TL-774 G = G12++ • Volkswagen TL-774 G = G12++

Technical data

Density at 20 °C	1,114 g/cm ³
Water content	3 % w/w max
pH value	8,6
Base	ethylene glycol with inhibitors
Color / appearance	bright red, clear
Flash point	122 °C
Boiling point	>170 °C
Odor	weak
Shelf life in original sealed container	36 months
Recommended storage temperature	-20 to +35 °C

Areas of application

For all cooling systems and engines in passenger cars (both with combustion engines as well as hybrid and battery electric vehicles), commercial vehicles, motorcycles, buses, agricultural and construction machinery as well as stationary engines and equipment that require cooling system protection of this quality. Especially for all-alloy engines in which a special aluminum protection is required at higher temperatures.

Application

Clean the cooling system with LIQUI MOLY Radiator

Cleaner (part no. 3320). Then empty this and rinse with plenty of water. Fill with radiator antifreeze KFS 12++ and water according to the mixing table and the manufacturer's instructions. We recommend distilled water for this. Depending on water hardness and quality, dilution with tap water is also possible. Disposal according to the local regulations. Change interval according to manufacturer's instructions. Store undiluted only. Miscible with coolants based on ethylene glycol.

MIXING TABLE

Frost protection	Water	Protection up to
1 part	2 parts	-20 °C
1 part	1 parts	-40 °C
2 parts	1 part	-68 °C

Available pack sizes

1 l Canister plastic	21134
	D-GB-I-E-P
5 l Canister plastic	21135
	D-GB-I-E-P
20 l Canister plastic	21136
	D-GB-I-E-P
60 l Black plate barrel	21137
	D-GB
200 l Black plate barrel	21304
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.