

Product information

megol Motorenoel HD-C3 SAE 15W-40



Description

Multigrade motor oil that is particularly suitable for year-round use as a universal oil. Thanks to its selected base oils and additive combination, suitable for use in both diesel and gasoline engines with and without catalytic converter, including those with a turbocharger. Also recommended for older vehicles (youngtimers).

Range of applications: Passenger cars, trucks, construction and agricultural machinery.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Approvals

ACEA A3 • ACEA B4 • ACEA E2 • API SL • API CF • API CG-4 • MAN M 3275-1

Meguin also recommends this product for vehicles that are subject to the following specifications

Allison C4 • Caterpillar TO-2 • Mack EO-L • MB 228.3 • MB 229.1 • MTU Typ 2 • Peugeot Citroen (PSA) B71 2295 • Volvo VDS

Characteristic data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,87 g/cm ³ DIN 51757
Viscosity at 40 °C	100 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,4 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	145 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-33 °C DIN ISO 3016
Evaporation loss (Noack)	10,8 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,9 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L4,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	4729 D-GB-F-HR-RUS-GR
4 l Canister plastic	6478 D-GB-F-HR-RUS-GR
5 l Canister plastic	4728 D-GB-F-HR-RUS-GR
20 l Canister plastic	4727 D-GB
60 l Drum sheet metal	4725 D-GB
200 l Drum sheet metal	4716 D-GB
1.000 l Deposit container	9754 D-GB
1 l Bulk goods	6892 D-GB