

Motorbike 4T 15W-50 Offroad

Description

High-performance motor oil based on synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear are just as much par for the course as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

Properties

- high shear stability
- optimum lubrication under all operating conditions
- optimum stability to aging
- especially suitable for wet clutches
- tested for the use with catalytic converters
- high wear resistance
- guarantees low oil consumption
- outstanding engine cleanliness

Specifications

API SP • JASO MA2

Technical data

| | |
|---------------------------|--|
| SAE class (engine oils) | 15W-50 SAE J 300 |
| Density at 15 °C | 0,870 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 140,0 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 18,3 mm ² /s ASTM D 7042-04 |
| Viscosity index | 145 DIN ISO 2909 |
| Viscosity at -20 °C (CCS) | <= 7000 mPas ASTM D5293 |
| Pour point | -30 °C DIN ISO 3016 |
| Evaporation loss (Noack) | 10,6 % CEC-L-40-A-93 |
| Flash point | 230 °C DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g DIN 51575 |
| Color number (ASTM) | L 2,0 DIN ISO 2049 |

Areas of application

Specially developed for air and water-cooled 4-stroke



engines exposed to extreme loads off-road. For the sporty driver. Suitable for Enduro and motocross motorbikes, ATVs, SxS and snowmobiles with and without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

| | |
|----------------------|-------------------|
| 1 l Canister plastic | 3057 D-BOOKLET |
| 4 l Canister plastic | 3058 D-BOOKLET |

Our information is based on thorough research and may be considered reliable, although not legally binding.