

Molygen New Generation 10W-30



Description

High performance low-friction motor oil for year-round use. The combination of unconventional base oils and advanced additive technology as well as the special Molygen additive ensures that the motor oil is of low viscosity with a high shear stability and reliably prevents the formation of deposits, significantly reducing frictional losses in the engine and providing the optimum protection from wear. This results in fuel savings and an extended service life for the engine.

Properties

- excellent wear resistance
- friction and wear reducing
- smooth engine running
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- outstanding shear resistance
- excellent high and low temperature behavior
- outstanding lubrication reliability
- miscible with all commercially available motor oils
- optimum stability to aging

Specifications / Approvals

API SP • ILSAC GF-6A

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford • GM • GM 6094 M • Honda • Hyundai • Isuzu • Kia • Mazda • Mitsubishi • Nissan • Subaru • Suzuki • Toyota

Technical data

SAE class (engine oils)	10W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	66,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	<= 60000 mPas ASTM D 4684
Viscosity at -25 °C (CCS)	>= 7000 mPas ASTM D 5293
Viscosity index	156 DIN ISO 2909
HTHS at 150°C	>= 2,9 mPas ASTM D 5481

Technical data

Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	8,2 % CEC-L-40-A-93
Flash point	238 °C DIN ISO 2592
Total base number	7,1 mg KOH/g DIN ISO 3771
Sulfate ash	< 0,8 g/100g DIN 51575
Color / appearance	green-brown, fluorescent

Areas of application

Optimum for modern Asian and American gasoline engines with multi-valve technology and turbocharging with and without charge air cooling. For the protection and value conservation of the engine during long intervals between oil changes and when there are extreme engine requirements.

Application

The operating instructions of the vehicle and engine manufacturers must be followed. Can be mixed with all commercially-available motor oils. Optimum effect obtained only when used on its own (i.e. no mixing).

Available pack sizes

1 l Canister plastic	9975 BOOKLET
4 l Canister plastic	20797 BOOKLET
5 l Canister plastic	9978 BOOKLET
205 l Black plate barrel	8422 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.