Product information

PI 36/08/18/2026

Motorbike Gear Oil 75W-140 (GL5)

Description

Fully synthetic high-pressure gear oil of API GL-5 performance class based on high-quality base oils and additives. Ensures easy, precise shifting operations and offers outstanding wear protection and optimum viscosity-temperature properties, even under extreme conditions.



Properties

- excellent wear resistance
- outstanding corrosion protection
- reduces transmission noise
- wide viscosity range

Available pack sizes

500 ml Can plastic	3072 DA-DE-EN-ES-FI-FR-NL-NO-PT-SV

Specifications / Approvals

API GL5

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

SAE class (gear oils)	75W-140 SAE J306
Density at 15 °C	0,875 g/cm³ DIN 51757
Viscosity at 40 °C	179 mm²/s ASTM D 7042-04
Viscosity at 100 °C	25 mm²/s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	172 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	208 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Areas of application

For transmissions and final drives operating under maximum load. Note the transmission manufacturer's instructions.

Application

Note the transmission manufacturer's instructions. Mixable with all branded gear oils. Optimum effect only when the product is used unmixed.

Available pack sizes

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com