

Motorbike 4T Synth 5W-40 Offroad Race

Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear are just as much par for the course as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

Properties

- optimum lubrication in extreme operating conditions
- high resistance to aging
- high shear stability
- guarantees low oil consumption
- tested for the use with catalytic converters
- outstanding engine cleanliness
- especially suitable for wet clutches
- excellent wear resistance

Specifications

API SP • JASO MA2

Technical data

| | |
|---------------------------|---|
| SAE class (engine oils) | 5W-40 SAE J300 |
| Density at 15 °C | 0,845 g/cm ³ DIN 51757 |
| Viscosity at 40 °C | 84,0 mm ² /s ASTM D 7042-04 |
| Viscosity at 100 °C | 13,8 mm ² /s ASTM D 7042-04 |
| Viscosity index | 170 DIN ISO 2909 |
| Viscosity at -30 °C (CCS) | ≤ 6600 mPas ASTM D5293 |
| HTHS at 150°C | ≥ 3,5 mPas ASTM D5481 |
| Pour point | -51 °C DIN ISO 3016 |
| Evaporation loss (Noack) | 6,0 % CEC-L-40-A-93 |
| Flash point | 230 °C DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g DIN 51575 |



Technical data

| | |
|---------------------|--------------|
| Color number (ASTM) | L 2,0 |
| | DIN ISO 2049 |

Areas of application

Specially developed for air and water-cooled 4-stroke engines exposed to extreme loads off-road. For the sporty driver. Suitable for Enduro and motocross motorbikes, ATVs, SxS and snowmobiles with and without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

| | |
|----------------------|-------------------|
| 1 l Canister plastic | 3018 D-BOOKLET |
| 4 l Canister plastic | 3019 D-BOOKLET |

Our information is based on thorough research and may be considered reliable, although not legally binding.