# Product information

PI 36/11/11/2026

## Motorbike 4T 5W-40 HC Street




### Description

High-performance motor oil. For maximum performance and protection of the engine under all operating conditions. Ensures optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear. Guarantees smooth engagement and disengagement as well as gear shifting. Tested on engines with catalytic converters.

### Properties

- outstanding engine cleanliness
- optimum stability to aging
- high shear stability
- high wear resistance
- guarantees low oil consumption
- tested for the use with catalytic converters
- optimum lubrication under all operating conditions
- especially suitable for wet clutches

### Specifications / Approvals

API SP • JASO MA2

### Technical data

| | |
|---|---|
| Viscosity SAE class | 5W-40<br>SAE J300 |
| Density at 15 °C | 0,850 g/cm³<br>DIN 51757 |
| Viscosity at 40 °C | 85,0 mm²/s<br>ASTM D 7042-04 |
| Viscosity at 100 °C | 14,3 mm²/s<br>ASTM D 7042-04 |
| Viscosity index | 175<br>DIN ISO 2909 |
| Viscosity at -30 °C (CCS) | <= 6600 mPas<br>ASTM D 5293 |
| HTHS at 150°C | ⩾ 3,5 mPas<br>ASTM D 5481 |
| Pour point | -36 °C<br>DIN ISO 2909 |
| Evaporation loss (Noack) | 11,0 %<br>ASTM D 5800 B |
| Flash point | 228 °C<br>DIN ISO 2592 |
| Total base number | 7,0 mg KOH/g<br>DIN ISO 3771 |
| Sulfate ash | 0,8 g/100g<br>DIN 51575 |
| Color number (ASTM) | L 2,0<br>DIN ISO 2049 |
| Oil base | Advanced Full Synthetic |

### Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

### Application

Note the vehicle and engine manufacturers' operating instructions. **Note:** Optimum effectiveness only when the product is used unmixed.

### Available pack sizes

| | |
|---|---|
| 1 l Canister plastic | 20750<br>AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 1 l Canister plastic | 23234<br>AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 4 l Canister plastic | 20751<br>AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 4 l Canister plastic | 23235<br>AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH |
| 20 l Canister plastic | 21226<br>DE-EN-ES-FR-IT-PT |
| 60 l Black plate barrel | 20752<br>DE-EN-ES-FR-IT-PT |
| 205 l Black plate barrel | 21122<br>DE-EN-ES-FR-IT-PT |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com