

Octane Plus



Description

Self-mixing combination of active agents for universal use. Increases the research octane number (RON) of the fuel by 2 – 4 points, depending on the RON. Prevents engine damage due to knocking combustion by improving the performance of the fuel and ensures lower fuel consumption thanks to the increased octane number.

Properties

- improves performance
- increases the octane number
- prevents engine damage caused by knocking combustion

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Shelf life in original sealed container	60 months
Color / appearance	yellowish, clear
Odor	characteristic
Density at 20 °C	0,8118 g/ml
Flash point	>61 °C
Mineral oil content	95,51 %

Areas of application

For increasing the octane number of gasolines in vehicles without particulate filters.

Comment

Attention: Only available for order outside Europe.

Application

150 ml sufficient for 50 l gasoline. Fill directly into the tank and then refuel. Mixing takes place automatically.

Note: Do not store the product at temperatures > 39 °C for extended periods!

Available pack sizes

150 ml Can sheet metal	2956
	GB-GR-I
150 ml Can sheet metal	7144
	ALGERIEN-GB-ARAB-F
150 ml Can sheet metal	8351
	GB-ARAB-F
150 ml Can sheet metal	8355
	D-E-P
150 ml Can sheet metal	21993
	MX
200 l Black plate barrel	8858
	D-GB