

Octane Plus



Description

Self-mixing combination of active agents for universal use. Increases the research octane number (RON) of the fuel by 2 – 4 points, depending on the RON. Prevents engine damage due to knocking combustion by improving the performance of the fuel and ensures lower fuel consumption thanks to the increased octane number.

Properties

- improves performance
- increases the octane number
- prevents engine damage caused by knocking combustion

legally binding.

Technical data

Shelf life in original sealed container	60 months
Color / appearance	yellowish, clear
Odor	characteristic
Density at 20 °C	0,8118 g/ml
Flash point	>61 °C
Mineral oil content	95,51 %

Areas of application

For increasing the octane number of gasolines in vehicles without particulate filters.

Comment

Attention: Only available for order outside Europe.

Application

150 ml sufficient for 50 l gasoline. Fill directly into the tank and then refuel. Mixing takes place automatically.

Note: Do not store the product at temperatures > 39 °C for extended periods!

Available pack sizes

150 ml Can sheet metal	2956
	GB-GR-I
150 ml Can sheet metal	8351
	AR-EN-FR
150 ml Can sheet metal	8355
	DE-ES-PT
150 ml Can sheet metal	21993
	MXES
200 l Black plate barrel	8858
	DE-EN

Our information is based on thorough research and may be considered reliable, although not