

Top Tec 6600 0W-20



Description

Premium low-friction motor oil based on synthetic technology. Ensures optimum lubrication and outstanding lubricating film stability as well as minimum wear and the smallest deposits even under extreme loads. Ideally suited for engines with start/stop system. Guarantees maximum performance with low fuel consumption.

Properties

- smooth engine running
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- excellent high and low temperature behavior
- optimum stability to aging
- optimum oil pressure under all operating conditions
- high lubrication reliability
- long engine service life
- saves fuel and reduces pollutant emissions
- high shear stability
- excellent wear protection

Specifications / Approvals

ACEA C5, C6 • API SQ • BMW Longlife-17 FE+ • ILSAC GF-7A • Jaguar / Land Rover STJLR.03.5006 • MB-Approval 229.71 • MB-Approval 229.72 • Opel OV 040 1547 - A20

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Chrysler MS-12145 • Fiat 9.55535-GSX • Ford WSS-M2C 947-B1 • Ford WSS-M2C 954-A1 • Ford WSS-M2C 962-A1

Technical data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	43 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481

Technical data

Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Areas of application

For gasoline and diesel vehicles. Specially developed for the requirements of BMW, Mercedes-Benz, Opel and other manufacturers.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21410 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	21411 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Canister plastic	21412 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Bag-in-Box	21959 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	21442 DE-EN

Product information

PI 39/07/03/2025



Top Tec 6600 0W-20

Available pack sizes

205 l Black 21443
plate barrel DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.